.040" Aluminum 24GA Steel Gutter LT G-1 Horizontal = 310 psf G-1 Horizontal = 290 psf G-2 Vertical = 20 psf G-2 Vertical = 40 psfG-3 Static = 430 psf ANSI/SPRI GD-1 CERTIFIED: G-3 Static = 430 psf Roof Membrane #10-13x1" S.S. Panhead Woodscrew 12" On Center Gutter Water Cut-Off Mastic Universal Single Ply Sealant Termination Bar #9 S.S. Washered Woodscrew 6" On Center #9 S.S. Washered Woodscrew (1) Per Bracket 7" Gutter LT Bracket 18GA (24" o.c. Max.) - Gutter Bracket and Fasteners provided. **QUANTITIES:** - Term Bar and fasteners NOT provided. Lineal Feet (10'-0" Lengths*): Outside Miters**: Optional Welded PRINT APPROVAL: (Surcharge Applies) Optional Welded (Surcharge Applies) Inside Miters**: Architect and/or Contractor shall verify all Optional Welded (Surcharge Applies) Right End Caps**:_____[dimensions, sizes, and quantities, All products to be installed in strict accordance Optional Welded (Surcharge Applies) Left End Caps**: with Drexel's printed instructions. Approved By: * Optional lengths available up to 20'-0" Date: ** Standard riveted MATERIAL: PROJECT: ARCHITECT: ROOFING CONTRACTOR:



REPRESENTATIVE:

41 North Lawn Ave / Elmsford, NY 10523 Ph. 914-347-8157

Fax 914-347-8191 web: www.tsmny.com email: sales@tsmny.com

Our Shop is Your Shop!

4	☐ 24GA	☐ .040" AL
╛	Other:	
-1		

Finish:

Color:

Effective Date: 8/8/17

B.Z.M.

Approved By: R.A.

Drawn By: